

HYDRO-RAIN®

Built for Speed®

HRC 100 C

A straightforward, user-friendly sprinkler controller which combines operating simplicity with feature-rich flexibility. For starters, the HRC 100 C is enclosed in an indoor/outdoor UL® approved case and is equipped with 4, 6, 9 or 12 watering stations. The HRC 100 C offers three independent programs – A and B and C – with up to four start times per program. Water conservation features? Of course! The HRC 100 C's water budgeting feature allows you to set watering durations from 10 to 200 percent of the programmed time, in 10 percent increments. There's even a station advance button that lets you skip to the next station while watering. Plus, you'll appreciate the simplicity of the large, easy-to-read LCD display, as well as the big buttons and dial – the perfect enhancements for easy user operation.



*Lid and power cord supplied, not shown

BUILT FOR SPEED ADVANTAGES

- **Fast to Program**—Large dial, oversized LCD display, make programming quick and easy.
- **Fast to Install**—Factory-installed plug-and-go power cord means no in-field transformer wiring is required.
- **Hinged Panel**—Door allows quick and easy access to valve wiring (shown on back).

BUILT FOR GREEN ADVANTAGES

- **Watering Budgeting**—Match seasonal watering requirements by increasing or decreasing the durations of the stations in any of the two programs from 10%~200% of base schedule.
- **Rain Delay**—Rain sensor bypass technology allows manual or automatic rain delay of 24-hours, 48-hours and 72-hours.
- **24 Volt Out Rain Sensor Terminals**—Make installation of wireless rain sensor receiver quick and convenient.

FEATURES AND BENEFITS

- **Three Programs**—Programs A, B and C offer multi-use and flexible watering schedules by days of the week, even or odd days, or at intervals of 1 to 32 days.
- **4 Start Times Per Program**—Flexibility to manage schedules for variable plant requirements and soil types.
- **Program Data Safely Stored**—Power out? No worries! All programming information is stored with battery backup.

MODELS SKU DESCRIPTION

HRC-100-C-04	04054	4-Station Indoor/Outdoor Controller
HRC-100-C-06	04056	6-Station Indoor/Outdoor Controller
HRC-100-C-09	04059	9-Station Indoor/Outdoor Controller
HRC-100-C-12	04052	12-Station Indoor/Outdoor Controller
HRC-100-C-04L	04054P	4-Station Indoor/Outdoor Controller with custom logo
HRC-100-C-06L	04056P	6-Station Indoor/Outdoor Controller with custom logo
HRC-100-C-09L	04059P	9-Station Indoor/Outdoor Controller with custom logo
HRC-100-C-12L	04052P	12-Station Indoor/Outdoor Controller with custom logo

HOW TO SPECIFY

HRC 100 C 09

MODEL	STATIONS
Controller	9



HYDRO-RAIN®

Built for Speed®

HRC 100 C

- **Manual Advance**—One-button station affords convenience of quick select and advance during manual watering.
- **Indoor/Outdoor UL® Cabinet**—Weather tight and locking for safety, security and peace of mind.
- **Three Year Unconditional Parts Warranty**—Hydro-Rain® warrants that its product will be free from defects for a minimum of three years from the date of purchase.

OPERATING SPECIFICATIONS

- **Station Timing:** From 1–240 minutes
- **Automatic Starts:** Up to 12 start times per day
- **Programming Schedule:** Days of week, watering intervals and odd/even days
- **Rain Delay:** Setting for 24, 48 and 72 hours
- **Water Budgeting:** Adjusts for seasonal watering demands (10% to 200% in 10% increments)

ELECTRICAL SPECIFICATIONS

- **Transformer Output:** 24VAC/26VAC, 600mA
- **Battery Backup:** 3V lithium (program saved in non-volatile memory)
- **Surge Protection:** Primary input has built-in MOV (metal oxide varistor), valve wire MOV protects against lightning strikes
- **UL/CL:** Approved
- **Wire Terminal:** Tool-less & Color Coded
- **Pump Start Terminal**



PN 04004-36 rF